



### Specifications

- Material : S45C
- Hardness : HRC 22 - 28
- Surface treatment: Black phosphated coating
- Thread Accuracy : ISO4H
- Perpendicularity : 0.002 ~ 0.007

### Order Method (Order Example)

<b>AN6</b>	<b>30</b>	<b>1.5</b>
Product NO	d	Pitch

Product NO.	d X pitch	Dimension(mm)						Adapter sleeve	washer
		D	d1	g	b	h	H		
		mm	mm	mm	mm	mm	mm		
AN02	M15×1	25	21	21	4	2	5	-	AW02
AN03	M17×1	28	24	24	4	2	5	-	AW03
AN04	M20×1	32	26	28	4	2	6	04	AW04
AN05	M25×1.5	38	32	34	5	2	7	05	AW05
AN06	M30×1.5	45	38	41	5	2	7	06	AW06
AN07	M35×1.5	52	44	48	5	2	8	07	AW07
AN08	M40×1.5	58	50	53	6	2.5	9	08	AW08
AN09	M45×1.5	65	56	60	6	2.5	10	09	AW09
AN10	M50×1.5	70	61	65	6	2.5	11	10	AW10
AN11	M55×2	75	67	69	7	3	11	11	AW11
AN12	M60×2	80	73	74	7	3	11	12	AW12
AN13	M65×2	85	79	79	7	3	12	13	AW13
AN14	M70×2	92	85	85	8	3.5	12	14	AW14
AN15	M75×2	98	90	91	8	3.5	13	15	AW15
AN16	M80×2	105	95	98	8	3.5	15	16	AW16
AN17	M85×2	110	102	103	8	3.5	16	17	AW17
AN18	M90×2	120	108	112	10	4	16	18	AW18
AN19	M95×2	125	113	117	10	4	17	19	AW19
AN20	M100×2	130	120	122	10	4	18	20	AW20
AN21	M105×2	140	126	130	12	5	18	21	AW21
AN22	M110×2	145	133	135	12	5	19	22	AW22
AN23	M115×2	150	137	140	12	5	19	-	AW23
AN24	M120×2	155	138	145	12	5	20	24	AW24
AN25	M125×2	160	148	150	12	5	21	-	AW25
AN26	M130×2	165	149	155	12	5	21	26	AW26
AN27	M135×2	175	160	163	14	6	22	-	AW27
AN28	M140×2	180	160	168	14	6	22	28	AW28
AN29	M145×2	190	172	178	14	6	24	-	AW29
AN30	M150×2	195	171	183	14	6	24	30	AW30
AN31	M155×3	200	182	186	16	7	25	-	-
AN32	M160×3	210	182	196	16	7	25	32	AW32
AN33	M165×3	210	193	196	16	7	26	-	-
AN34	M170×3	220	193	206	16	7	26	34	AW34
AN36	M180×3	230	203	214	18	8	27	36	AW36
AN38	M190×3	240	214	224	18	8	28	38	AW38
AN40	M200×3	250	226	234	18	8	29	40	AW40