

CI-2001A/N/BN | Weighing Indicator



CI-2001AN



CI-2001BN

Features

- ▶ Wall-mounted / Small Indicator
- ▶ Easy weight setting (Full Digital Calibration)
- ▶ Weight Back-Up (Saving of weight at sudden power failure)
- ▶ Watch-Dog circuitry (System restoration)

Option

- ▶ RS-422/485
- ▶ RTC (Real Time Clock, CI-2001BN)
- ▶ USB
- ▶ Panel Guide

Specifications

Model	CI-2001AN	CI-2001BN
Load cell excitation voltage	DC 5V	
No. of Load cell connection	4ea (350Ω)	
Zero Adjustment Range	0.05 mV ~ 5 mV	
Load cell Input Range	0 mV/V ~ 3.2 mV/V	
Input sensitivity	2μV/D (OIML, KC, NTEP), 0.5 μV/D (Non-approval)	
A/D Internal resolution	1/200,000	
A/D external resolution	1/5,000 (OIML, KC, NTEP) 1/30,000 (Non-approval)	
A/D conversion speed	Up to 10 times/sec	
Display	6digits LED (Character Height: 14mm)	5digits LCD (Character Height: 25mm)
Key	6 Function keys	
Interface	RS-232C	
Operating Power	DC 12V Adaptor	
Operating Temp	-10 ~ 40 °C	
Material	ABS	
Product Size (W x D x H)	186 x 58 x 85mm	
Product Weight	0.5kg	