



### Specifications

- Material : S45C
- Hardness : HRC 22 - 28
- Surface treatment: Black phosphated coating
- Thread Accuracy : ISO4H
- Perpendicularity : 0.002 ~ 0.007

### Order Method (Order Example)

<b>DN</b>	<b>30</b>	<b>1.5</b>
Product NO	d	Pitch

Product NO.	d X pitch	Dimension(mm)					Set screw		Mass g
		D	d1	T	t	H	n-m	N-m	
		mm	mm	mm	mm	mm			
DN4	M4×0.5	11.5	8	10	2.8	5	M3	0.9	2
DN5	M5×0.5	13.5	9	11	2.8	5	M3	0.9	3
DN6	M6×0.75	14.5	10	12	3.1	5.5	M3	0.9	4
DN8	M8×1	16	13	14	3.9	7.0	M3	0.9	8
DN8	M8×0.75	16	13	14	3.9	7.0	M3	0.9	8
DN10	M10×1	20	16	17	4.5	8.0	M4	2	12
DN10	M10×0.75	20	16	17	4.5	8.0	M4	2	12
DN10-S	M10×1	20	16	17	4.5	8.0	2-M4	2	12
DN12	M12×1	22	18	19	4.5	8.0	M4	2	14
DN12-S	M12×1	22	18	19	4.5	8.0	2-M4	2	14
DN15	M15×1	25	21	22	4.5	8.0	2-M4	2	16
DN17	M17×1	28	23	24	5.4	10	2-M5	4.5	24
DN17-S	M17×1	30	25	24	9	13	2-M5	4.5	34
DN20	M20×1	32	27	28	5.4	10	2-M5	4.5	32
DN20-S	M20×1	35	26	29.3	7	11	2-M5	4.5	42
DN25	M25×1.5	38	33	34	6.5	12	2-M6	8	52
DN30	M30×1.5	45	40	41	6.5	12	2-M6	8	74
DN35	M35×1.5	52	47	48	6.5	12	2-M6	8	100
DN40	M40×1.5	58	52	53	8	14	2-M6	8	134