



Specifications

- Material : S45C
- Hardness : HRC 22 - 28
- Surface treatment: Black phosphated coating
- Thread Accuracy : ISO4H
- Perpendicularity : 0.002 ~ 0.007

Order Method (Order Example)

KSNT6	30	1.5
Product NO	d	Pitch

Product NO.	d X pitch	Dimension(mm)							Set Screw		Mass
		D	d1	d2	d3	H	g	t	mm	N·m	g
KSNT2	M15×1	33	26	25	16	16	4	2.5	M5	4.5	85
KSNT3	M17×1	37	29	30	18	18	5	2.5	M6	8	110
KSNT4	M20×1	40	32	32	21	18	5	2.5	M6	8	120
KSNT5	M25×1.5	44	36	36	26	20	5	2.5	M6	8	140
KSNT6	M30×1.5	49	41	41	32	20	5	2.5	M6	8	180
KSNT7	M35×1.5	54	46	46	38	22	5	2.5	M6	8	210
KSNT8	M40×1.5	65	56	56	42	22	6	3	M8	18	330
KSNT9	M45×1.5	70	61	61	48	22	6	3	M8	18	370
KSNT10	M50×1.5	75	65	65	52	25	7	3	M8	18	450
KSNT11	M55×2	85	74	75	58	25	7	3	M8	18	590
KSNT12	M60×2	90	78	79	62	26	8	4	M8	18	670
KSNT13	M65×2	95	83	84	68	28	8	4	M8	18	780
KSNT14	M70×2	100	88	89	72	28	8	4	M8	18	830
KSNT15	M75×2	105	93	94	77	28	8	4	M8	18	880
KSNT16	M80×2	110	98	96	83	32	8	4	M8	18	990
KSNT17	M85×2	120	107	106	88	32	10	4	M10	35	1,270
KSNT18	M90×2	125	112	111	93	32	10	4	M10	35	1,320
KSNT19	M95×2	130	117	116	98	32	10	4	M10	35	1,380
KSNT20	M100×2	135	122	121	103	32	10	4	M10	35	1,430
KSNT22	M110×2	145	132	130	112	32	10	4	M10	35	1,600
KSNT24	M120×2	155	142	140	122	32	10	4	M10	35	1,760
KSNT26	M130×2	165	152	150	132	32	12	5	M10	35	1,870
KSNT28	M140×2	175	162	160	142	32	14	6	M10	35	1,980
KSNT30	M150×2	185	172	170	152	32	14	6	M10	35	2,150
KSNT32	M160×2	195	182	180	162	32	14	6	M10	35	2,350
KSNT34	M170×2	205	192	190	172	32	14	6	M10	35	2,550
KSNT36	M180×2	215	200	200	182	32	16	7	M10	35	2,640
KSNT38	M190×2	225	210	210	192	32	16	7	M10	35	2,750
KSNT40	M200×2	235	220	220	202	32	18	8	M10	35	2,850