



### Specifications

- Material : S45C
- Hardness : HRC 22 - 28
- Surface treatment: Black phosphated coating
- Thread Accuracy : ISO4H
- Perpendicularity : 0.002 ~ 0.007

### Order Method (Order Example)

<b>KZMF</b>	<b>30</b>	<b>1.5</b>
Product NO	d	Pitch

Product NO.	d X pitch	Dimension(mm)							Set Screw		Mass
		D	d1	H	n-g	b	t	C	m	N·m	g
		mm	mm	mm	mm	mm	mm	mm			
KZMF20	M20×1	38	33	16	3-4	-	2	-	M6	4.5	110
KZMF25	M25×1.5	38	33	18	3-5	-	2	-	M6	8	120
KZMF30	M30×1.5	45	40	18	3-5	-	2	-	M6	8	140
KZMF35	M35×1.5	52	47	18	3-5	-	2	-	M8	18	170
KZMF40	M40×1.5	58	52	20	3-6	-	2.5	-	M8	18	210
KZMF45	M45×1.5	65	59	20	3-6	-	2.5	-	M8	18	300
KZMF50	M50×1.5	70	64	20	3-6	-	2.5	-	M8	18	310
KZMF55	M55×2	75	68	22	3-7	6	3	65	M8	18	350
KZMF60	M60×2	80	73	22	3-7	6	3	70	M8	18	430
KZMF65	M65×2	85	78	22	3-7	6	3	75	M8	18	450
KZMF70	M70×2	92	84	24	3-8	6	3.5	81	M8	18	550
KZMF75	M75×2	98	90	24	3-8	6	3.5	87	M8	18	590
KZMF80	M80×2	105	96	24	3-8	7	3.5	93	M8	18	810
KZMF85	M85×2	110	102	24	6-8	7	3.5	98	M8	18	900
KZMF90	M90×2	120	108	26	6-10	7	4	105	M8	18	1,100
KZMF95	M95×2	125	113	26	6-10	7	4	110	M8	18	1,150
KZMF100	M100×2	130	118	26	6-10	7	4	115	M8	18	1,200
KZMF110	M110×2	145	132	28	6-10	7	4	128	M10	35	1,350
KZMF120	M120×2	155	142	30	6-12	7	5	138	M10	35	1,600
KZMF130	M130×2	165	152	30	6-12	7	5	148	M10	35	1,850
KZMF140	M140×2	180	165	32	6-12	7	5	160	M10	35	2,450
KZMF150	M150×2	195	180	32	6-12	7	5	173	M10	35	2,800
KZMF160	M160×3	210	190	34	6-14	8	6	185	M10	35	3,400
KZMF170	M170×3	220	200	34	6-14	8	6	195	M10	35	3,500
KZMF180	M180×3	230	205	36	6-16	8	7	205	M12	60	3,650
KZMF190	M190×3	240	215	36	6-16	8	7	215	M12	60	3,900
KZMF200	M200×3	250	225	38	6-16	8	7	225	M12	60	4,400