

NT-200 Series | Weighing Indicator



NT-200A



NT-201A



NT-200S



NT-201S

Features

- ▶ Easy weight setting (Full Digital Calibration)
- ▶ Weight Back-Up (Saving of weight at sudden power failure)
- ▶ Clear LED/LCD display
- ▶ Waterproof design (IP65) (NT-200S/201S)

Option

- ▶ RS-422/485
- ▶ RTC (Real Time Clock)

Specifications

Model	NT-200A/S	NT-201A/S
Load cell excitation voltage	DC 5V	
No. of Load cell connection	6ea (350Ω)	
Zero Adjustment Range	0.05 mV ~ 5 mV	
Load cell Input Range	0 mV/V ~ 2.0 mV/V	
Input sensitivity	2μV/D (OIML, KC, NTEP), 0.5 μV/D (Non-approval)	
A/D Internal resolution	1/200,000	
A/D external resolution	1/5,000 (OIML, KC, NTEP) 1/20,000 (Non-approval, 2mV/V load cell)	
A/D conversion speed	Up to 60 times/sec	
Display	6digits LED (Character Height: 25mm)	6digits LCD (Character Height: 25mm)
Key	6 Function keys	
Interface	RS-232C	
Operating Power	DC 9V Adaptor	
Operating Temp	-10 ~ 40 °C	
Material	NT-200A/201A : ABS, NT-200S/201S : Stainless Steel	
Product Size (W x D x H)	NT-200A/201A : 200 x 53 x 97mm, NT-200S/201S : 200 x 53 x 130mm	
Product Weight	NT-200A/201A : 0.5kg, NT-200S/201S : 1kg	