



Features

- Set screw can be fitted at the shaft direction.

Specifications

- Material : S45C
- Hardness : HRC 22 - 28
- Surface treatment: Black phosphated coating
- Thread Accuracy : ISO4H
- Perpendicularity : 0.002 ~ 0.007

Order Method (Order Example)

ZMVT6	30	1.5
Product NO	d	Pitch

Product NO.	d X pitch	Dimension(mm)									Set Screw		Mass g
		D	d1	d2	d3	H	J1	J2	N1	N2	m	N · m	
		mm	mm	mm	mm	mm	mm	mm	mm	mm			
ZMVT5	M25×1.5	42	33.5	35	26	20	32.5	11	4.3	5	M6	8	120
ZMVT6	M30×1.5	48	39	40	32	20	40.5	11	4.3	5	M6	8	150
ZMVT7	M35×1.5	53	44	47	38	20	45.5	11	4.3	5	M6	8	180
ZMVT8	M40×1.5	58	49	52	42	22	50.5	12	4.3	5	M6	8	210
ZMVT9	M45×1.5	68	56.5	58	48	22	58	12	4.3	5	M6	8	300
ZMVT10	M50×1.5	70	60	63	52	24	61.5	12	4.3	5	M6	8	310
ZMVT11	M55×1.5	75	65	70	58	24	66.5	13	4.3	5	M6	8	350
ZMVT12	M60×1.5	84	72	75	62	24	74.5	13	5.3	5	M6	8	450
ZMVT13	M65×1.5	88	76	80	68	25	78.5	13	5.3	5	M6	8	480
ZMVT14	M70×1.5	95	83	86	72	26	85	14	5.3	7.9	M10	35	570
ZMVT15	M75×1.5	100	88	91	77	26	88	13	6.4	7.9	M10	35	610
ZMVT16	M80×2	110	96	97	83	30	95	16	6.4	7.9	M10	35	910
ZMVT17	M85×2	115	100	102	88	32	100	17	6.4	9.6	M12	60	1,050
ZMVT18	M90×2	120	105	110	93	32	108	17	6.4	9.6	M12	60	1,100
ZMVT19	M95×2	125	110	114	98	32	113	17	6.4	9.6	M12	60	1,150
ZMVT20	M100×2	130	115	120	103	32	118	17	6.4	9.6	M12	60	1,200
ZMVT22	M110×2	140	128	132	112	32	125	17	6.4	9.6	M12	60	1,350
ZMVT24	M120×2	155	138	142	122	32	140	17	6.4	9.6	M12	60	1,700
ZMVT26	M130×3	165	148	156	132	32	153	17	6.4	9.6	M12	60	1,900
ZMVT28	M140×3	180	160	166	142	32	165	17	6.4	9.6	M12	60	2,250
ZMVT30	M150×3	195	173	180	152	32	175	17	6.4	9.6	M12	60	2,450
ZMVT32	M160×3	205	182	190	162	32	185	17	8.4	9.6	M12	60	2,900
ZMVT34	M170×3	215	192	205	172	32	195	17	8.4	9.6	M12	60	3,150
ZMVT36	M180×3	230	205	215	182	32	210	17	8.4	9.6	M12	60	3,650
ZMVT38	M190×3	240	215	225	192	32	224	17	8.4	9.6	M12	60	3,850
ZMVT40	M200×3	245	223	237	202	32	229	17	8.4	9.6	M12	60	3,700